

View Online at <https://aerobasegroup.com/nsn/5995-01-522-0636>

Furnished Items:

Connector

End Application:

Aps137 hpd

Termination Type:

Prod terminal 2nd end all conductors

Conductor Quantity:

3

Cable Assemblylength:

90.000 inches

Product Name:

Cable assembly .030 pins to bnc male connt.

Individual Conductor Length:

0.250 inches 2nd end all conductors

Branch Quantity:

2

Special Features:

Includes: bnc male connector (p/n8915) brass 1/2 hard per qq-b-626, alloy 360 with polytetrafluoroethylene l-p-403 insulator finished with tri-metal plating, center contact silver plated; strain-relief boot (p/nsr-58), buna-n-40 durometer, black; coaxial cable (p/n c-1000/0) rg 58 c/u 20 awg 19x.0071 tinned copper, .195 od black pvc jacket, 50 ohm; y -block (p/ny-1000) molded nylon type 6 or 6/6 black hardware stainless steel; two wires (p/n w-200/color 22 awg 65x40 tinned copper pvc insulation .017 wall .070 o.D. UI1160 maximum temp 60 degrees c, maximum voltage 600 v, red one 1.5 inches long, center contact, black one 8.00 inches long; 2 contact pins (p/n 0564) .030 diameter x .250 long pin plug, mat: leaded nickel copper, finish: gold plated per mil-g-45204, type 1; heat shrink tubing (p/n0146/0) rnf-100 black 3/32 dia. X .750

Material:

Rubber 5th position sleeve all conductors

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A077a0