NSN 5995-01-524-3236

Radio Frequency Cable Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5995-01-524-3236

Cross Sectional Shape: Round Overall Length: 144.000 inches Tempurature Rating: -46.0 degrees celsius and 71.0 degrees celsius Environmental Protection: Fungus resistant End Application: Nan 5865-01-470-4744; target acquistion subsystem. Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color: Black core sleeve all conductors
Overall Length: 144.000 inches Tempurature Rating: -46.0 degrees celsius and 71.0 degrees celsius Environmental Protection: Fungus resistant End Application: Nsn 5865-01-470-4744; target acquistion subsytem. Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
144.000 inches Tempurature Rating: -46.0 degrees celsius and 71.0 degrees celsius Environmental Protection: Fungus resistant End Application: Nsn 5865-01-470-4744; target acquistion subsytem. Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144* +/-6*; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195* o.D. Color:
Tempurature Rating: -46.0 degrees celsius and 71.0 degrees celsius Environmental Protection: Fungus resistant End Application: Nsn 5865-01-470-4744; target acquistion subsytem. Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
-46.0 degrees celsius and 71.0 degrees celsius Environmental Protection: Fungus resistant End Application: Nsn 5865-01-470-4744; target acquistion subsytem. Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Environmental Protection: Fungus resistant End Application: Nsn 5865-01-470-4744; target acquistion subsytem. Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Fungus resistant End Application: Nsn 5865-01-470-4744; target acquistion subsytem. Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
End Application: Nsn 5865-01-470-4744; target acquistion subsytem. Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-ter 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Nsn 5865-01-470-4744; target acquistion subsytem. Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-ter 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-tofor 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-tofor 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-t for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-t for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Color:
Plack care along all conductors
black core sleeve all corrouctors
Style Designator:
External connectors
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A077a0