## NSN 5995-01-524-3236

Radio Frequency Cable Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5995-01-524-3236

Cross Sectional Shape: Round Overall Length: 144.000 inches Tempurature Rating: -46.0 degrees celsius and 71.0 degrees celsius Environmental Protection: Fungus resistant End Application: Nan 5865-01-470-4744; target acquistion subsystem. Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color: Black core sleeve all conductors
Overall Length:  144.000 inches  Tempurature Rating:  -46.0 degrees celsius and 71.0 degrees celsius  Environmental Protection:  Fungus resistant  End Application:  Nsn 5865-01-470-4744; target acquistion subsytem.  Termination Type:  Connector plug 2nd end single conductor  Conductor Quantity:  2  Product Name:  Cable assembly  Terminal Manufacturer Identifying Reference Number:  1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features:  Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
144.000 inches Tempurature Rating:  -46.0 degrees celsius and 71.0 degrees celsius Environmental Protection: Fungus resistant End Application: Nsn 5865-01-470-4744; target acquistion subsytem. Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144* +/-6*; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195* o.D. Color:
Tempurature Rating:  -46.0 degrees celsius and 71.0 degrees celsius  Environmental Protection:  Fungus resistant  End Application:  Nsn 5865-01-470-4744; target acquistion subsytem.  Termination Type:  Connector plug 2nd end single conductor  Conductor Quantity: 2  Product Name:  Cable assembly  Terminal Manufacturer Identifying Reference Number:  1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features:  Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
-46.0 degrees celsius and 71.0 degrees celsius  Environmental Protection: Fungus resistant  End Application: Nsn 5865-01-470-4744; target acquistion subsytem.  Termination Type: Connector plug 2nd end single conductor  Conductor Quantity: 2  Product Name: Cable assembly  Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
Environmental Protection: Fungus resistant End Application: Nsn 5865-01-470-4744; target acquistion subsytem. Termination Type: Connector plug 2nd end single conductor Conductor Quantity: 2 Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Fungus resistant  End Application:  Nsn 5865-01-470-4744; target acquistion subsytem.  Termination Type:  Connector plug 2nd end single conductor  Conductor Quantity: 2  Product Name:  Cable assembly  Terminal Manufacturer Identifying Reference Number:  1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features:  Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
End Application:  Nsn 5865-01-470-4744; target acquistion subsytem.  Termination Type:  Connector plug 2nd end single conductor  Conductor Quantity: 2  Product Name:  Cable assembly  Terminal Manufacturer Identifying Reference Number:  1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features:  Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-ter 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
Nsn 5865-01-470-4744; target acquistion subsytem.  Termination Type:  Connector plug 2nd end single conductor  Conductor Quantity:  2  Product Name:  Cable assembly  Terminal Manufacturer Identifying Reference Number:  1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features:  Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-ter 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
Termination Type:  Connector plug 2nd end single conductor  Conductor Quantity:  2  Product Name:  Cable assembly  Terminal Manufacturer Identifying Reference Number:  1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features:  Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-tofor 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
Connector plug 2nd end single conductor  Conductor Quantity:  2  Product Name:  Cable assembly  Terminal Manufacturer Identifying Reference Number:  1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features:  Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-tofor 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
Conductor Quantity:  2  Product Name: Cable assembly  Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-t for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
Product Name: Cable assembly Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D. Color:
Product Name: Cable assembly  Terminal Manufacturer Identifying Reference Number: 1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features: Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
Cable assembly  Terminal Manufacturer Identifying Reference Number:  1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features:  Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
Terminal Manufacturer Identifying Reference Number:  1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features:  Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
1a1w230p2 (1a32a7-pt4) 2nd end single conductor  Special Features:  Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
Special Features:  Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-t for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
Cable assembly, rf; rf switch-1 to power splitter; humidity; 95% @ 4 degrees c; vibration: military ground vehicle; resistant to salt fog-for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
for 48 hours; length 144" +/- 6"; cable/wire thermax m17/060-rg142 50 ohm, flex coax, fep, .195" o.D.  Color:
Color:
Plack care along all conductors
black core sleeve all corrouctors
Style Designator:
External connectors
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A077a0