

View Online at <https://aerobasegroup.com/nsn/5995-01-559-0434>

**Overall Length:**

119.000 inches

**End Application:**

Mh-60s helo designation

**Conductor Quantity:**

2

**Conductor Form:**

Solid, tubular all conductors

**Product Name:**

Coax cable assembly

**Special Features:**

M/k w/i cockpit. The cable assembly is in the forward left run between the forward receiver r-2390/j7 and bulkhead disconnect sta 239. Cable: (tms-times microwave systems) specification miltech 230. Connectors: p1-replaceable, self-locking sma male, tms p/n 48689; p2-replaceable, self-locking tnc male, tms p/n 48606. Environmental and mechanical characteristics in accordance with miltech 230. Temp range: neg 55 degrees c to pos 110 degrees c. Bend radius: 1.15 in min. Test frequency: 2.0 to 18 ghz. Insertion loss at 23 degrees c, maximum 4.10 db. Vswr, max: 1.40. Marking information: marker a-red (p9016/j7, fwd rdr warn rcvr), marker b-white (ae30485 rev c s/n), marker c-red (p9032/j9032, sta 239 disc).

**Style Designator:**

Dual receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A077a0