NSN 5996-00-054-4627

Direct Current Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-054-4627 **Overall Length:** 2.020 inches **Overall Height:** 0.625 inches **Overall Width:** 1.145 inches **Environmental Protection:** Salt spray resistant and shock resistant and vibration **Vibration Resistance Range In Hertz:** +10.0 to 40.0 **Vibration Resistance Amplitude:** 0.02 inches total excursion **Shock Resistance Rating In Gravitational Units:** 10.0 **Operating Tempurature Range:** -25.0/+85.0 degrees celsius **Storage Tempurature Range:** -55.0 to 85.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 10000.0 feet **Inclosure Type:** Encased **Operating Control Method:** Automatic Installation Design: Module **Circuit Construction Type: Signal Voltage Rating Per Channel:** 11.000 volts output Impedance Rating Per Channel: 100.000 megohms input channel **Shock Pulse Duration Time:** 11.0 milliseconds **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:**

8 pin external

NSN 5996-00-054-4627

Direct Current Amplifier - Page 2 of 2



External	Dc Ope	erating	Voltage	In Volts:

15.0 single voltage

Precious Material And Location:

Term., surf. Gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200