

NSN 5996-00-054-4628 Direct Current Amplifier - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5996-00-054-4628 **Overall Length:** 2.810 inches **Overall Height:** 0.990 inches **Overall Width:** 1.320 inches **Environmental Protection:** Salt spray resistant and shock resistant and vibration **Vibration Resistance Range In Hertz:** +10.0 to 40.0 **Vibration Resistance Amplitude:** 0.02 inches total excursion **Shock Resistance Rating In Gravitational Units:** 10.0 **Operating Tempurature Range:** -25.0/+75.0 degrees celsius **Storage Tempurature Range:** -55.0 to 75.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 10000.0 feet **Inclosure Type:** Encased **Operating Control Method:** Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Impedance Rating Per Channel:

200.000 kilohms input channel

Pulse Peak Amplitude Per Channel:

9.000 volts operating channel

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Pin bottom

NSN 5996-00-054-4628

Direct Current Amplifier - Page 2 of 2



Connection (Contact	Type And	Quantity:
--------------	---------	----------	-----------

8 pin external

External Dc Operating Voltage In Volts:

15.0 single voltage

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32200