NSN 5996-00-110-5476

Direct Current Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-110-5476

Overall Length:

Between 0.700 inches and 0.775 inches

Overall Height:

Between 0.400 inches and 0.500 inches

Overall Width:

Between 0.450 inches and 0.510 inches

Environmental Protection:

Moisture proof and salt spray resistant and shock resistant and vibration

Shock Resistance Rating In Gravitational Units:

100.0

Operating Tempurature Range:

-55.0 to 100.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Identification Designator:

acitation Debignat

3500-07-502-0134

Inclosure Type:

Encased

Operating Control Method:

Automatic

Installation Design:

Panel

Control Type:

Local

Circuit Construction Type:

Solid state

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Wire lead terminals left side and wire lead terminals right side

Connection Contact Type And Quantity:

1 wire lead terminals external and 2 wire lead terminals external

External Dc Operating Voltage In Volts:

12.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5996-00-110-5476 Direct Current Amplifier - Page 2 of 2

Fiig: A32200

