## NSN 5996-00-110-5476

Direct Current Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-110-5476 **Overall Length:** Between 0.700 inches and 0.775 inches **Overall Height:** Between 0.400 inches and 0.500 inches Overall Width: Between 0.450 inches and 0.510 inches **Environmental Protection:** Moisture proof and salt spray resistant and shock resistant and vibration **Shock Resistance Rating In Gravitational Units:** 100.0 **Operating Tempurature Range:** -55.0 to 100.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 3500-07-502-0134 **Inclosure Type:** Encased **Operating Control Method:** Automatic Installation Design: Panel **Control Type:** Local **Circuit Construction Type:** Solid state **Shock Pulse Duration Time:** 11.0 milliseconds **Connection Type And Location:** Wire lead terminals left side and wire lead terminals right side **Connection Contact Type And Quantity:** 1 wire lead terminals external and 2 wire lead terminals external **External Dc Operating Voltage In Volts:** 12.0 single voltage Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## **NSN 5996-00-110-5476**Direct Current Amplifier - Page 2 of 2



Fiig:

A32200