## NSN 5996-00-114-1541

Direct Current Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-114-1541

Polishility Indicator						
Reliability Indicator:						
Not established						
Inclosure Material: Plastic						
Overall Length:  Between 1.950 inches and 2.025 inches						
Overall Height:						
Between 0.400 inches and 0.460 inches						
Overall Width:						
Between 0.450 inches and 0.510 inches						
Operating Tempurature Range:						
-55.0 to 100.0 degrees celsius						
Storage Tempurature Range:						
-65.0 to 125.0 degrees celsius						
Average Life Measurement:						
Not rated						
Basic Shape Style:						
Rectangular or square						
Inclosure Type:						
Encapsulated						
Operating Control Method:						
Automatic						
Installation Design:						
Module						
Control Type:						
Remote						
Circuit Construction Type:						
Solid state						
Average Power Rating Per Channel:						
220.0 milliwatts input						
Signal Voltage Rating Per Channel:						
5.000 volts input						
Connection Type And Location:						
Wire lead terminals left side and wire lead terminals right side						
Connection Contact Type And Quantity:						
4 wire lead terminals external						
External Dc Operating Voltage In Volts:						
12.0 single voltage						
Fsc Application Data:						
Communication equipment, miscellaneous						
Shelf Life:						

N/a

## NSN 5996-00-114-1541

Direct Current Amplifier - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200