NSN 5996-00-123-2157

Intermediate Frequency Amplifier - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5996-00-123-2157



Overall Length: 5.000 inches **Overall Height:** 2.500 inches **Overall Width:** 0.750 inches **Environmental Protection:** General purpose **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** Not rated **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 89-683570-07397 Phase Shift Angle In Deg: Any acceptable **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Operating Control Method:** Automatic Installation Design: Mechanical **Control Type:** Remote **Circuit Construction Type:** Solid state **Switching Rate Per Second:** Any acceptable Frequency Shift: Any acceptable Frequency Per Channel: 21.4 megahertz operating channel Frequency Adjustment Type: Continuous

NSN 5996-00-123-2157

Intermediate Frequency Amplifier - Page 2 of 2



Variation Frequency Rating In Decibels:
6.0
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
Not rated
Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
100.0 decibels
Impedance Rating Per Channel:
50.000 ohms output channel
Distortion Type And Percent:
Any acceptable
Indicator Device Type And Quantity:
1 light
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Integral cable w/coaxial plug top
Connection Contact Type And Quantity:
2 integral cable w/coaxial plug external
External Dc Operating Voltage In Volts:
12.0 single voltage
Intermediate Frequency Bandpass:
30.0 megahertz
Fsc Application Data:
Receiving set countermeasures
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32200