NSN 5996-00-136-1240

Radio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-136-1240

Overall Length:
5.500 inches
Overall Height:
2.810 inches
Environmental Protection:
Salt spray resistant and shock resistant and vibration
Shock Resistance Rating In Gravitational Units:
20.0
Operating Tempurature Range:
-25.0 to 144.0 degrees fahrenheit
Average Life Measurement:
Not rated
End Application:
Radio set an/grc-66
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
10000.0 meters
Inclosure Type:
Encased
Operating Control Method:
Automatic
Automatic Installation Design:
Installation Design:
Installation Design: Mechanical
Installation Design: Mechanical Control Type:
Installation Design: Mechanical Control Type: Remote
Installation Design: Mechanical Control Type: Remote Circuit Construction Type:
Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state
Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel:
Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 4.4 gigahertz operating channel and 5.0 gigahertz operating channel
Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 4.4 gigahertz operating channel and 5.0 gigahertz operating channel Average Power Rating Per Channel:
Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 4.4 gigahertz operating channel and 5.0 gigahertz operating channel Average Power Rating Per Channel: 100.0 milliwatts input
Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 4.4 gigahertz operating channel and 5.0 gigahertz operating channel Average Power Rating Per Channel: 100.0 milliwatts input Overall Gain:
Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 4.4 gigahertz operating channel and 5.0 gigahertz operating channel Average Power Rating Per Channel: 100.0 milliwatts input Overall Gain: 22.5 decibels
Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 4.4 gigahertz operating channel and 5.0 gigahertz operating channel Average Power Rating Per Channel: 100.0 milliwatts input Overall Gain: 22.5 decibels Impedance Rating Per Channel:
Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 4.4 gigahertz operating channel and 5.0 gigahertz operating channel Average Power Rating Per Channel: 100.0 milliwatts input Overall Gain: 22.5 decibels Impedance Rating Per Channel: 50.000 ohms output channel
Installation Design: Mechanical Control Type: Remote Circuit Construction Type: Solid state Frequency Per Channel: 4.4 gigahertz operating channel and 5.0 gigahertz operating channel Average Power Rating Per Channel: 100.0 milliwatts input Overall Gain: 22.5 decibels Impedance Rating Per Channel: 50.000 ohms output channel Connection Type And Location:

Fsc Application Data:

Miscellaneous communication equipment

NSN 5996-00-136-1240

Radio Frequency Amplifier - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200