NSN 5996-00-140-8182

Audio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-140-8182 **Overall Length:** 19.000 inches **Overall Height:** 8.750 inches **Overall Width:** 8.000 inches **Environmental Protection:** General purpose **Vibration Resistance Range In Hertz:** Not rated **Individual Section Quantity: Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range: Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Open **Operating Control Method:** Manual Installation Design: Rack **Control Type:** Local **Circuit Construction Type:** Electron tube Frequency Per Channel: 40.0 hertz 2nd operating channel **Attenuation In Decibels:** 22.0 **Average Power Rating Per Channel:** 80.0 watts output Signal Voltage Rating Per Channel: Not rated **Overall Gain:**

68.0 decibels

NSN 5996-00-140-8182

Audio Frequency Amplifier - Page 2 of 2



Impedance Rating Per Channel:
70.000 ohms input channel
Distortion Type And Percent:
2.0 frequency and 5.0 frequency
Indicator Device Type And Quantity:
1 light
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Receptacle, power bottom
Operating Ac Frequency In Hertz:
60.0 single voltage
Connection Contact Type And Quantity:
2 receptacle, power external
External Ac Operating Voltage In Volts:
117.0 single voltage
Phase:
Single
Special Features:
Tube testing circuitry within the amplifier
Fsc Application Data:
Transponder
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32200