NSN 5996-00-140-8635

Intermediate Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-140-8635 **Overall Length:** 5.250 inches **Overall Height:** 1.531 inches **Overall Width:** 2.188 inches **Environmental Protection:** Moisture proof and salt spray resistant and shock resistant and vibration **Operating Tempurature Range:** +45.0/+120.0 degrees fahrenheit Storage Tempurature Range: -65.0 to 155.0 degrees fahrenheit **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 10000.0 feet **Inclosure Type: Encased Operating Control Method:** Automatic Installation Design: Mechanical **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 637.5 megahertz operating channel and 763.5 megahertz operating channel **Overall Gain:** 20.0 decibels **Impedance Rating Per Channel:** 50.000 ohms input channel **Connection Type And Location:** Solder lug front and receptacle, coaxial left side and receptacle, coaxial right side **Connection Contact Type And Quantity:** 2 receptacle, coaxial external and 3 solder lug external **External Dc Operating Voltage In Volts:**

2 receptacle, coaxial external and 3 so External Dc Operating Voltage In Vo 24.0 single voltage Intermediate Frequency Bandpass: 700.0 megahertz

NSN 5996-00-140-8635

Intermediate Frequency Amplifier - Page 2 of 2



| | Life: |
|--|-------|
| | |
| | |

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200