

NSN 5996-00-164-5843

Radio Frequency Amplifier - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5996-00-164-5843	
Overall Length:	
5.250 inches	
Overall Height:	
2.080 inches	
Overall Width:	
1.750 inches	
Environmental Protection:	
Salt spray resistant and shock resistant and vibration	

Vibration Resistance Range In Hertz:

+5.0 to 55.0

Vibration Resistance Amplitude:

0.06 inches total excursion

Shock Resistance Rating In Gravitational Units:

20.0

Operating Tempurature Range:

+0.0 to 85.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Identification Designator:

A51D-10-M13-1091

Maximum Operating Altitude Rating:

10000.000 feet

Inclosure Type:

Encased

Installation Design:

Mechanical

Circuit Construction Type:

Solid state

Impedance Rating Per Channel:

50.000 ohms output channel

Distortion Type And Percent:

20.0 frequency

Maximum Continuous Operating Time In Hours:

Not rated

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Dual panel jack left side and dual panel jack right side

Connection Contact Type And Quantity:

2 single panel jack external

NSN 5996-00-164-5843

Radio Frequency Amplifier - Page 2 of 2



External Dc Operating Voltage In Volts:

28.0 single voltage

Features Provided:

Automatic gain control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200