NSN 5996-00-192-2101



Radio Frequency Amplifier - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5996-00-192-2101 **Overall Length:** 1.200 inches **Overall Height:** 0.250 inches **Overall Width:** 0.800 inches **Environmental Protection:** Moisture proof **Vibration Resistance Range In Hertz:** +100.0 to 2000.0 **Vibration Resistance Amplitude:** 20.0 gravitational units **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Hermetically sealed Installation Design: Module **Circuit Construction Type:** Solid state Frequency Per Channel: Not rated **Attenuation In Decibels: Average Power Rating Per Channel:** 5.0 watts output **Signal Voltage Rating Per Channel:** 20.000 volts input **Overall Gain:** 0.1 decibels Impedance Rating Per Channel:

10.000 ohms output channel

Maximum Continuous Operating Time In Hours:

1000.0

NSN 5996-00-192-2101

Radio Frequency Amplifier - Page 2 of 2



Printed circuit bottom

Connection Contact Type And Quantity:

10 printed circuit external

Fsc Application Data:

Antenna-receiver-transmitter group, missile tracking

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200