Radio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-192-2101

Overall Length:
1.200 inches
Overall Height:
0.250 inches
Overall Width:
0.800 inches
Environmental Protection:
Moisture proof
Vibration Resistance Range In Hertz:
+100.0 to 2000.0
Vibration Resistance Amplitude:
20.0 gravitational units
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Hermetically sealed
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Per Channel:
Not rated
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
5.0 watts output
Signal Voltage Rating Per Channel:
20.000 volts input
Overall Gain:
0.1 decibels
Impedance Rating Per Channel:
10.000 ohms output channel
Maximum Continuous Operating Time In Hours:
1000.0

NSN 5996-00-192-2101

Radio Frequency Amplifier - Page 2 of 2



Connection Type And Location:

Printed circuit bottom

Connection Contact Type And Quantity:

10 printed circuit external

Fsc Application Data:

Antenna-receiver-transmitter group, missile tracking

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200