NSN 5996-00-196-0695

Direct Current Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-196-0695

Overall Length:
1.800 inches
Overall Height:
0.780 inches
Overall Width:
1.200 inches
Environmental Protection:
Moisture proof and shock resistant and vibration
Vibration Resistance Range In Hertz:
+2.0/+500.0
Vibration Resistance Amplitude:
10.0 gravitational units
Shock Resistance Rating In Gravitational Units:
25.0
Operating Tempurature Range:
-2.0/+85.0 degrees celsius
Storage Tempurature Range:
-55.0/+100.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Mechanical and module
Control Type:
Remote
Circuit Construction Type:
Solid state
Impedance Rating Per Channel:
1.000 megohms input channel
Shock Pulse Duration Time:
40.0 milliseconds
Connection Type And Location:
Pin bottom
Connection Contact Type And Quantity:
8 pin external
External Dc Operating Voltage In Volts:
15.0 single voltage

NSN 5996-00-196-0695

Direct Current Amplifier - Page 2 of 2



Precious	Material	And I	Location:

Terminal surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200