NSN 5996-00-255-3116

Electronic Control Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-255-3116

The state of the s	_`
Vibration Resistance Range In Hertz:	
Not rated	
Individual Section Quantity:	
1	
Shock Resistance Rating In Gravitational Units:	
Not rated	
Operating Tempurature Range:	
+40.0 to 149.0 degrees fahrenheit	
Average Life Measurement:	
Not rated	
Basic Shape Style:	
Rectangular or square	
Maximum Operating Altitude Rating:	
Not rated	
Inclosure Type:	
Encased	
Operating Control Method:	
Automatic	
Installation Design:	
Module	
Control Type:	
Local	
Circuit Construction Type:	
Solid state	
Frequency Per Channel:	
400.0 hertz output channel	
Attenuation In Decibels:	
Not rated	
Average Power Rating Per Channel:	
Not rated	
Signal Voltage Rating Per Channel:	
800.000 millivolts input	
Overall Gain:	
46.2 volts	
Impedance Rating Per Channel:	
Not rated	
Pulse Peak Amplitude Per Channel:	
Not rated	
Signal Data Type Per Channel:	
Input channel error	
Maximum Continuous Operating Time In Hours:	
Not rated	

Not rated

NSN 5996-00-255-3116

Electronic Control Amplifier - Page 2 of 2



Connection Type And Location:
Receptacle, power rear
Operating Ac Frequency In Hertz:
400.0 single voltage
Connection Contact Type And Quantity:
14 receptacle, power external
External Ac Operating Voltage In Volts:
115.0 single voltage
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A32200