

View Online at <https://aerobasegroup.com/nsn/5996-00-255-3141>

Vibration Resistance Range In Hertz:

Not rated

Individual Section Quantity:

2

Shock Resistance Rating In Gravitational Units:

Not rated

Operating Temperature Range:

+40.0 to 149.0 degrees fahrenheit

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Maximum Operating Altitude Rating:

Not rated

Inclosure Type:

Encased

Operating Control Method:

Manual

Installation Design:

Module

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

400.0 hertz output channel

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

30.000 volts input

Overall Gain:

Not rated

Impedance Rating Per Channel:

Not rated

Pulse Peak Amplitude Per Channel:

Not rated

Signal Data Type Per Channel:

Output channel error

Indicator Device Type And Quantity:

1 audible alarm and 1 light

Maximum Continuous Operating Time In Hours:

Not rated

Connection Type And Location:

Receptacle, power rear

Operating Ac Frequency In Hertz:

400.0 1st voltage

Connection Contact Type And Quantity:

20 receptacle, power external

External Dc Operating Voltage In Volts:

28.0 single voltage

External Ac Operating Voltage In Volts:

30.0 1st voltage

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200