## NSN 5996-00-259-0305

Video Amplifier - Page 1 of 2

**Vibration Resistance Range In Hertz:** 

Overall Length: 2.250 inches Overall Height: 0.600 inches Overall Width: 1.500 inches



View Online at https://aerobasegroup.com/nsn/5996-00-259-0305

Not rated
<b>Shock Resistance Rating In Gravitational Units:</b>
Not rated
Operating Tempurature Range:
-54.0 to 71.0 degrees celsius
Average Life Rating:
10000.0
Average Life Measurement:
Hours
Average Life Rating In Hours:
10000.0
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
50000.0 feet
Inclosure Type:
Encased
Installation Design:
Mechanical
Circuit Construction Type:
Solid state
Frequency Per Channel:
Not rated
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
Not rated
Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Overall Gain: 26.0 decibels
26.0 decibels

Any acceptable

## NSN 5996-00-259-0305

Video Amplifier - Page 2 of 2



Pulse Rise Time Per Channel:
1.000 nanoseconds output channel
Pulse Decay Time Per Channel:
1.000 nanoseconds output channel
Polarity Per Channel:
Any acceptable
Pulse Repetition Rate Per Channel:
Any acceptable
Pulse Peak Amplitude Per Channel:
3.150 volts output channel
Err Default:
Err default
Pulse Modulation Type Per Channel:
Any acceptable
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Receptacle, coaxial left side and receptacle, coaxial right side
Connection Contact Type And Quantity:
2 receptacle, coaxial internal
External Dc Operating Voltage In Volts:
15.0 single voltage
Fsc Application Data:
Synchronizer-exciter, radar set, airborne
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A32200