NSN 5996-00-268-8410

Overall Length:

Intermediate Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-268-8410

8.500 inches
Overall Height:
1.500 inches
Overall Width:
3.480 inches
Environmental Protection:
Dust tight
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
-20.0 to 55.0 degrees celsius
Average Life Measurement:
Hours
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Encased
Installation Design:
Panel
Circuit Construction Type:
Solid state
Frequency Per Channel:
30.0 megahertz operating channel
Average Power Rating Per Channel:
1.95 watts input
Signal Voltage Rating Per Channel:
22.000 microvolts input
Overall Gain:
80.0 decibels
Impedance Rating Per Channel:
50.000 ohms operating channel
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Receptacle, power rear and receptacle, coaxial rear and receptacle, coaxial rear and receptacle, coaxial rear
Connection Contact Type And Quantity:
9 receptacle, power internal and 1 receptacle, coaxial internal and 1 receptacle, coaxial internal and 1 receptacle, coaxial internal

NSN 5996-00-268-8410

Intermediate Frequency Amplifier - Page 2 of 2



External Dc Operating Voltage In Volts:

15.0 single voltage

Intermediate Frequency Bandpass:

2.0 megahertz

Special Features:

Ti 6340.5, a80501, pg 5-29

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200