Radio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-398-9651

View Online at https://aerobasegroup.com/nsn/5996-00-398-9651
Overall Length:
2.375 inches
Overall Height:
0.750 inches
Overall Width:
1.375 inches
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Inclosure Type:
Open
Operating Control Method:
Automatic
Installation Design:
Mechanical
Control Type:
Local
Circuit Construction Type:
Solid state
Frequency Per Channel:
Frequency Per Channel: 11.0 megahertz operating channel
11.0 megahertz operating channel
11.0 megahertz operating channel Average Power Rating Per Channel:
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain:
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels Impedance Rating Per Channel:
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels Impedance Rating Per Channel: 50.000 ohms operating channel
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location:
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Integral cable w/coaxial plug left side and receptacle, coaxial top
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Integral cable w/coaxial plug left side and receptacle, coaxial top Connection Contact Type And Quantity:
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Integral cable w/coaxial plug left side and receptacle, coaxial top Connection Contact Type And Quantity: 1 integral cable w/coaxial plug internal and 1 receptacle, coaxial internal
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Integral cable w/coaxial plug left side and receptacle, coaxial top Connection Contact Type And Quantity: 1 integral cable w/coaxial plug internal and 1 receptacle, coaxial internal External Dc Operating Voltage In Volts:
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Integral cable w/coaxial plug left side and receptacle, coaxial top Connection Contact Type And Quantity: 1 integral cable w/coaxial plug internal and 1 receptacle, coaxial internal External Dc Operating Voltage In Volts: 12.0 single voltage
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Integral cable w/coaxial plug left side and receptacle, coaxial top Connection Contact Type And Quantity: 1 integral cable w/coaxial plug internal and 1 receptacle, coaxial internal External Dc Operating Voltage In Volts: 12.0 single voltage
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Integral cable w/coaxial plug left side and receptacle, coaxial top Connection Contact Type And Quantity: 1 integral cable w/coaxial plug internal and 1 receptacle, coaxial internal External Dc Operating Voltage In Volts: 12.0 single voltage Fsc Application Data: Receiving set, countermeasures
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Integral cable w/coaxial plug left side and receptacle, coaxial top Connection Contact Type And Quantity: 1 integral cable w/coaxial plug internal and 1 receptacle, coaxial internal External Dc Operating Voltage In Volts: 12.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life:
 11.0 megahertz operating channel Average Power Rating Per Channel: 10.0 milliwatts output Overall Gain: 10.0 decibels Impedance Rating Per Channel: 50.000 ohms operating channel Connection Type And Location: Integral cable w/coaxial plug left side and receptacle, coaxial top Connection Contact Type And Quantity: 1 integral cable w/coaxial plug internal and 1 receptacle, coaxial internal External Dc Operating Voltage In Volts: 12.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a

No

NSN 5996-00-398-9651

Radio Frequency Amplifier - Page 2 of 2

Fiig: A32200

