

NSN 5996-00-406-4951 Electronic Control Amplifier - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5996-00-406-4951 **Overall Length:** 2.125 inches **Overall Diameter:** 1.250 inches **Environmental Protection:** Vibration and shock resistant and moisture proof **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -0.0 to 62.0 degrees celsius **Average Life Rating:** 200000.0 **Average Life Measurement: Average Life Rating In Hours:** 200000.0 **Basic Shape Style:** Cylindrical Phase Shift Angle In Deg: 90.0 input to output **Inclosure Type:** Hermetically sealed Installation Design: Mechanical **Circuit Construction Type:** 

Solid state

Frequency Per Channel:

400.0 hertz 1st input channel

**Variation Frequency Rating In Decibels:** 

2.0

**Attenuation In Decibels:** 

Not rated

**Average Power Rating Per Channel:** 

6.3 watts output

**Signal Voltage Rating Per Channel:** 

30.000 volts output

**Overall Gain:** 

Not rated

**Impedance Rating Per Channel:** 

12.000 kilohms input channel

## NSN 5996-00-406-4951

Electronic Control Amplifier - Page 2 of 2



Pulse Peak Amplitude Per Channel:
Not rated
Signal Data Type Per Channel:
Output channel proportional
<b>Maximum Continuous Operating Time In Hours:</b>
200000.0
Connection Type And Location:
Receptacle, power bottom
Connection Contact Type And Quantity:
7 receptacle, power external
External Dc Operating Voltage In Volts:
28.0 single voltage
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A32200