Electronic Control Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-406-4951

Overall Length:
2.125 inches
Overall Diameter:
1.250 inches
Environmental Protection:
Vibration and shock resistant and moisture proof
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
Not rated
Operating Tempurature Range:
-0.0 to 62.0 degrees celsius
Average Life Rating:
200000.0
Average Life Measurement:
Hours
Average Life Rating In Hours:
200000.0
Basic Shape Style:
Cylindrical
Phase Shift Angle In Deg:
90.0 input to output
Inclosure Type:
Hermetically sealed
Installation Design:
Mechanical
Circuit Construction Type:
Solid state
Frequency Per Channel:
400.0 hertz 1st input channel
Variation Frequency Rating In Decibels:
2.0
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
6.3 watts output
Signal Voltage Rating Per Channel:
30.000 volts output
Overall Gain:
Not rated
Impedance Rating Per Channel:
12.000 kilohms input channel

NSN 5996-00-406-4951

Electronic Control Amplifier - Page 2 of 2



Pulse Peak Amplitude Per Channel: Not rated Signal Data Type Per Channel: Output channel proportional Maximum Continuous Operating Time In Hours: 200000.0 **Connection Type And Location:** Receptacle, power bottom **Connection Contact Type And Quantity:** 7 receptacle, power external **External Dc Operating Voltage In Volts:** 28.0 single voltage Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A32200