NSN 5996-00-435-9393

Electronic Control Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-435-9393 **Overall Length:** 8.300 inches **Overall Height:** 4.500 inches **Overall Width:** 4.500 inches **Environmental Protection:** Dust tight and moisture proof and oil tight and salt spray resistant and shock resistant and vibration **Vibration Resistance Range In Hertz:** +5.0 to 500.0 **Vibration Resistance Amplitude:** 0.1 inches total excursion **Shock Resistance Rating In Gravitational Units:** 15.0 **Operating Tempurature Range:** -55.0 to 71.0 degrees celsius **Average Life Measurement:** Indefinite **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Operating Control Method:** Automatic Installation Design: Mechanical **Control Type:** Local **Circuit Construction Type:** Solid state Frequency Per Channel: 400.0 hertz 2nd output channel **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated Signal Voltage Rating Per Channel: Not rated

Overall Gain: Not rated

NSN 5996-00-435-9393

Electronic Control Amplifier - Page 2 of 2



| Impedance Rating Per Channel: |
|---|
| Not rated |
| Pulse Peak Amplitude Per Channel: |
| Not rated |
| Signal Data Type Per Channel: |
| 2nd output channel analog voltage |
| Maximum Continuous Operating Time In Hours: |
| Not rated |
| Shock Pulse Duration Time: |
| 11.0 milliseconds |
| Connection Type And Location: |
| Receptacle, power front |
| Connection Contact Type And Quantity: |
| 26 receptacle, power external |
| External Dc Operating Voltage In Volts: |
| 30.0 single voltage |
| Features Provided: |
| Automatic gain control |
| Fsc Application Data: |
| Compass, magnetic, mounted |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A32200 |
| |