NSN 5996-00-435-9393

Electronic Control Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-435-9393 **Overall Length:** 8.300 inches **Overall Height:** 4.500 inches **Overall Width:** 4.500 inches **Environmental Protection:** Dust tight and moisture proof and oil tight and salt spray resistant and shock resistant and vibration **Vibration Resistance Range In Hertz:** +5.0 to 500.0 **Vibration Resistance Amplitude:** 0.1 inches total excursion **Shock Resistance Rating In Gravitational Units:** 15.0 **Operating Tempurature Range:** -55.0 to 71.0 degrees celsius **Average Life Measurement:** Indefinite **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Operating Control Method:** Automatic Installation Design: Mechanical **Control Type:** Local **Circuit Construction Type:** Solid state Frequency Per Channel: 400.0 hertz 2nd output channel **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated Signal Voltage Rating Per Channel: Not rated

Overall Gain: Not rated

NSN 5996-00-435-9393

Electronic Control Amplifier - Page 2 of 2



Impedance Rating Per Channel:
Not rated
Pulse Peak Amplitude Per Channel:
Not rated
Signal Data Type Per Channel:
2nd output channel analog voltage
Maximum Continuous Operating Time In Hours:
Not rated
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Receptacle, power front
Connection Contact Type And Quantity:
26 receptacle, power external
External Dc Operating Voltage In Volts:
30.0 single voltage
Features Provided:
Automatic gain control
Fsc Application Data:
Compass, magnetic, mounted
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32200