

View Online at <https://aerobasegroup.com/nsn/5996-00-437-8121>

Overall Length:

7.562 inches

Overall Height:

3.000 inches

Overall Width:

3.938 inches

Environmental Protection:

Vibration and shock resistant and moisture proof

Vibration Resistance Range In Hertz:

+5.0 to 33.0

Vibration Resistance Amplitude:

0.1 inches total excursion

Shock Resistance Rating In Gravitational Units:

50.0

Operating Temperature Range:

-28.0 to 65.0 degrees celsius

Average Life Rating:

25000.0

Average Life Measurement:

Hours

Average Life Rating In Hours:

25000.0

Basic Shape Style:

Rectangular or square

Maximum Operating Altitude Rating:

Not rated

Inclosure Type:

Encased

Installation Design:

Mechanical

Circuit Construction Type:

Solid state

Frequency Per Channel:

400.0 hertz 3rd input channel

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

26.000 volts input

Overall Gain:

74.0 volts

Impedance Rating Per Channel:

1.000 megohms input channel

Pulse Peak Amplitude Per Channel:

Not rated

Signal Data Type Per Channel:

3rd input channel synchro

Maximum Continuous Operating Time In Hours:

Not rated

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Receptacle, power right side

Operating Ac Frequency In Hertz:

400.0 single voltage

Connection Contact Type And Quantity:

6 receptacle, power internal and 12 receptacle, power internal

External Ac Operating Voltage In Volts:

120.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200