NSN 5996-00-462-2533

Direct Current Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-462-2533 **Inclosure Material:** Plastic **Overall Length:** Between 1.740 inches and 1.800 inches **Overall Height:** 0.780 inches **Overall Width:** Between 1.140 inches and 1.200 inches **Surface Luster:** Matte **Environmental Protection:** Shock resistant and vibration and weatherproof **Vibration Resistance Amplitude:** 10.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 25.0 **Operating Tempurature Range:** -20.0/+71.0 degrees celsius **Cubic Measure:** 1.243 cubic inches **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Inclosure Type:** Encapsulated **Installation Design:** Mechanical **Circuit Construction Type:** Solid state **Overall Gain:** 123.0 decibels **Shock Pulse Duration Time:** 40.0 milliseconds **Connection Type And Location:** Pin bottom **External Dc Operating Voltage In Volts:** 25.0 single voltage **External Ac Operating Voltage In Volts:** 40.0 single voltage

Color: Black

NSN 5996-00-462-2533

Direct Current Amplifier - Page 2 of 2



Precious	Material	∆nd ∣	Location:
riccious	iviale lai	Allu I	LUCALIUII.

Pin surface gold and pin plating silver

Precious Material:

Gold and silver

Fsc Application Data:

Test equipment, electronic shop, field maintenance

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200