NSN 5996-00-465-8261



Trigger Pulse Amplifier - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5996-00-465-8261 **Overall Length:** 9.470 inches **Overall Height:** 1.375 inches **Overall Width:** 6.062 inches **Environmental Protection:** Fungus proof **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -0.0 to 50.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 53b2rm-13499 **Maximum Operating Altitude Rating:** 15000.0 feet **Inclosure Type:** Encased **Operating Control Method:** Manual Installation Design: Module **Control Type:** Local **Circuit Construction Type:** Solid state Frequency Per Channel: Not rated **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated Signal Voltage Rating Per Channel: Not rated

Overall Gain: Not rated

NSN 5996-00-465-8261

Trigger Pulse Amplifier - Page 2 of 2



Impedance Rating Per Channel:
Not rated
Pulse Peak Amplitude Per Channel:
Not rated
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Receptacle, coaxial rear and printed circuit rear
Connection Contact Type And Quantity:
6 receptacle, coaxial external and 16 printed circuit external
External Dc Operating Voltage In Volts:
20.0 single voltage
Test Data Document:
13499-568-5627 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32200