## NSN 5996-00-653-2367

Electronic Control Amplifier - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5996-00-653-2367

Environmental Protection:
Fungus proof and moisture proof
Operating Tempurature Range:
-18.0/+85.0 degrees celsius
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
60.0 hertz output channel
Average Power Rating Per Channel:
6.0 watts output
•
Signal Voltage Rating Per Channel:
Signal Voltage Rating Per Channel: 60.000 volts any acceptable
60.000 volts any acceptable
60.000 volts any acceptable  External Dc Operating Voltage In Volts:
60.000 volts any acceptable  External Dc Operating Voltage In Volts:  1.0 1st voltage err-100
60.000 volts any acceptable  External Dc Operating Voltage In Volts:  1.0 1st voltage err-100  Shelf Life:
60.000 volts any acceptable  External Dc Operating Voltage In Volts:  1.0 1st voltage err-100  Shelf Life:  N/a
60.000 volts any acceptable  External Dc Operating Voltage In Volts:  1.0 1st voltage err-100  Shelf Life:  N/a
60.000 volts any acceptable  External Dc Operating Voltage In Volts:  1.0 1st voltage err-100  Shelf Life:  N/a  Unit Of Measure:
60.000 volts any acceptable  External Dc Operating Voltage In Volts:  1.0 1st voltage err-100  Shelf Life: N/a  Unit Of Measure:  Demilitarization:
60.000 volts any acceptable  External Dc Operating Voltage In Volts:  1.0 1st voltage err-100  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli
60.000 volts any acceptable  External Dc Operating Voltage In Volts:  1.0 1st voltage err-100  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  Yes - demil/mli  Fiig:
60.000 volts any acceptable  External Dc Operating Voltage In Volts:  1.0 1st voltage err-100  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  Yes - demil/mli  Fiig: