

View Online at <https://aerobasegroup.com/nsn/5996-00-725-8307>

**Overall Length:**

11.590 inches

**Overall Height:**

3.090 inches

**Overall Width:**

5.090 inches

**Environmental Protection:**

Moisture proof

**Vibration Resistance Range In Hertz:**

+40.0 to 70.0

**Individual Section Quantity:**

Any acceptable

**Vibration Resistance Amplitude:**

3.0 gravitational units

**Shock Resistance Rating In Gravitational Units:**

8.0

**Operating Temperature Range:**

+4.0 to 54.0 degrees celsius

**Average Life Rating:**

16000.0

**Average Life Measurement:**

Hours

**Average Life Rating In Hours:**

16000.0

**Basic Shape Style:**

Rectangular or square

**Identification Designator:**

2623146-10001

**Maximum Operating Altitude Rating:**

Not rated

**Inclosure Type:**

Encased

**Operating Control Method:**

Manual

**Installation Design:**

Portable

**Control Type:**

Local

**Circuit Construction Type:**

Solid state

**Switching Rate Per Second:**

Any acceptable

**Frequency Shift:**

Any acceptable

**Frequency Per Channel:**

1.0 kilohertz input channel and 150.0 megahertz input channel

**Frequency Adjustment Type:**

Continuous

**Attenuation In Decibels:**

Not rated

**Average Power Rating Per Channel:**

Not rated

**Signal Voltage Rating Per Channel:**

1.000 volts input

**Overall Gain:**

3.0 decibels

**Impedance Rating Per Channel:**

50.000 ohms input channel

**Distortion Type And Percent:**

5.0 frequency

**Maximum Continuous Operating Time In Hours:**

Not rated

**Shock Pulse Duration Time:**

30.0 microseconds

**Connection Type And Location:**

Receptacle, power rear

**Operating Ac Frequency In Hertz:**

60.0 single voltage

**Connection Contact Type And Quantity:**

3 receptacle, power internal

**External Ac Operating Voltage In Volts:**

115.0 single voltage

**Phase:**

Single

**Fsc Application Data:**

Test set, guided missile system

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32200