Electronic Control Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-759-6248

| Reliability Indicator: | |
|---|--|
| Not established | |
| Overall Length: | |
| 2.000 inches | |
| Overall Height: | |
| Between 1.830 inches and 2.330 inches | |
| Overall Width: | |
| 0.970 inches | |
| Operating Tempurature Range: | |
| -55.0/+90.0 degrees celsius | |
| Fragility Factor: | |
| Delicate | |
| Average Life Measurement: | |
| Not rated | |
| Basic Shape Style: | |
| Rectangular or square | |
| Maximum Operating Altitude Rating: | |
| 50000.0 feet | |
| Inclosure Type: | |
| Encapsulated | |
| Operating Control Method: | |
| Automatic | |
| Installation Design: | |
| Module | |
| Control Type: | |
| Remote | |
| Circuit Construction Type: | |
| Solid state | |
| Impedance Rating Per Channel: | |
| 150.000 kilohms input channel err-100 | |
| Connection Type And Location: | |
| Pin bottom | |
| Connection Contact Type And Quantity: | |
| 6 pin external | |
| External Dc Operating Voltage In Volts: | |
| 30.0 single voltage and 32.0 single voltage | |
| Special Markings: | |
| Top); r2; r1 | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |

NSN 5996-00-759-6248

Electronic Control Amplifier - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200