Direct Current Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-00-945-4234

| Overall Length: | |
|--------------------------|--|
| 1.120 inches | |
| Overall Height: | |
| 0.620 inches | |
| Overall Width: | |
| 1.120 inches | |
| Environmental Protect | ion: |
| Weatherproof | |
| Operating Tempuratur | e Range: |
| 25.0/+85.0 degrees cel | sius |
| Storage Tempurature | Range: |
| 55.0/+85.0 degrees cel | sius |
| Average Life Measure | nent: |
| Not rated | |
| Basic Shape Style: | |
| Rectangular or square | |
| nclosure Type: | |
| Encapsulated | |
| Operating Control Met | hod: |
| utomatic | |
| nstallation Design: | |
| lodule | |
| control Type: | |
| Remote | |
| Circuit Construction T | уре: |
| Solid state | |
| Average Power Rating | Per Channel: |
| 20.0 milliwatts output | |
| Overall Gain: | |
| 0000.0 volts | |
| mpedance Rating Per | Channel: |
| 5.0 kilohms output chan | nel and 10.0 megohms 2nd input channel and 10.0 megohms 1st input channel |
| External Dc Operating | Voltage In Volts: |
| 15.0 single voltage | |
| Test Data Document: | |
|)4071-r354009 drawing | (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specificati | on, standard or other document that may be referenced in a basic governing drawing) |
| Fsc Application Data: | |
| Trainer, weapon system | n, aircraft |
| Shelf Life: | |
| N/a | |

N/a

Unit Of Measure:

NSN 5996-00-945-4234

Direct Current Amplifier - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A32200

