NSN 5996-00-975-2789

Direct Current Amplifier - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5996-00-975-2789 |
|---|
| Inclosure Material: |
| Plastic |
| Overall Length: |
| 1.78125 inches |
| Overall Height: |
| 0.59375 inches |
| Overall Width: |
| 1.1875 inches |
| Environmental Protection: |
| General purpose |
| Average Life Measurement: |
| Not rated |
| Basic Shape Style: |
| Rectangular or square |
| Inclosure Type: |
| Encapsulated |
| Operating Control Method: |
| Automatic |
| Installation Design: |
| Module |
| Circuit Construction Type: |
| Solid state |
| Average Power Rating Per Channel: |
| 0.2 watts output |
| Overall Gain: |
| 96.0 volts |
| Impedance Rating Per Channel: |
| 300.000 kilohms operating channel |
| Connection Type And Location: |
| Pin bottom |
| Connection Contact Type And Quantity: |
| 8 pin external |
| External Dc Operating Voltage In Volts: |
| 15.0 single voltage |
| Criticality Code Justification: |
| Feat |
| Special Features: |
| |

Critical application: defense support program

Supplementary Features:

Pins identified by, 1, 2, 4, x, y, x, -, and +

Fsc Application Data:

Test set, elect. Equip.

NSN 5996-00-975-2789

Direct Current Amplifier - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200