NSN 5996-01-018-4654

Electronic Control Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-01-018-4654 **Overall Length:** 2.065 inches **Overall Height:** 1.255 inches **Overall Width:** 1.365 inches **Vibration Resistance Range In Hertz:** +5.0/+500.0 **Shock Resistance Rating In Gravitational Units:** 15.0 **Operating Tempurature Range:** -32.0/+100.0 degrees celsius **Average Life Rating:** 2000.0 **Average Life Measurement: Average Life Rating In Hours:** 2000.0 **Basic Shape Style:** Irregular **Identification Designator:** 930205-1c-82577 **Maximum Operating Altitude Rating:** 30000.0 feet **Inclosure Type:** Encased Installation Design: Module **Circuit Construction Type:** Solid state

Frequency Per Channel: 396.0 hertz input channel and 404.0 hertz input channel **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** 10.0 watts output **Signal Voltage Rating Per Channel:** 360.000 millivolts input **Overall Gain:** Not rated Impedance Rating Per Channel:

2.000 ohms output channel err-100

NSN 5996-01-018-4654 Electronic Control Amplifier - Page 2 of 2



Pulse Peak Amplitude Per Channel:
Not rated
Signal Data Type Per Channel:
Output channel servo
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Wire lead terminals left side
Connection Contact Type And Quantity:
8 wire lead terminals external
External Dc Operating Voltage In Volts:
28.0 single voltage
Precious Material And Location:
Terminals gold
Precious Material And Weight:
0.040 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A32200