Electronic Control Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-01-018-4654

Overall Length:
2.065 inches
Overall Height:
1.255 inches
Overall Width:
1.365 inches
Vibration Resistance Range In Hertz:
+5.0/+500.0
Shock Resistance Rating In Gravitational Units:
15.0
Operating Tempurature Range:
-32.0/+100.0 degrees celsius
Average Life Rating:
2000.0
Average Life Measurement:
Hours
Average Life Rating In Hours:
2000.0
Basic Shape Style:
Irregular
Identification Designator:
930205-1c-82577
Maximum Operating Altitude Rating:
30000.0 feet
Inclosure Type:
Encased
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Per Channel:
396.0 hertz input channel and 404.0 hertz input channel
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
10.0 watts output
Signal Voltage Rating Per Channel:
360.000 millivolts input
Overall Gain:
Not rated
Impedance Rating Per Channel:
2.000 ohms output channel err-100

NSN 5996-01-018-4654

Electronic Control Amplifier - Page 2 of 2



Pulse Peak Amplitude Per Channel: Not rated Signal Data Type Per Channel: Output channel servo Maximum Continuous Operating Time In Hours: Not rated **Connection Type And Location:** Wire lead terminals left side **Connection Contact Type And Quantity:** 8 wire lead terminals external **External Dc Operating Voltage In Volts:** 28.0 single voltage Precious Material And Location: Terminals gold **Precious Material And Weight:** 0.040 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig:

A32200

4322