## NSN 5996-01-026-1936

Radio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-01-026-1936 **Overall Length:** 3.000 inches **Overall Height:** 2.000 inches **Overall Width:** 1.040 inches **Environmental Protection:** Moisture proof and salt spray resistant and vibration **Vibration Resistance Range In Hertz:** Not rated **Individual Section Quantity: Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 800176p3-94117 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Installation Design:** Mechanical **Circuit Construction Type:** Solid state Frequency Per Channel: 60.0 megahertz operating channel err-100 **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** 200.0 milliwatts input Signal Voltage Rating Per Channel: Not rated **Overall Gain:** 11.2 decibels

Impedance Rating Per Channel:

50.000 ohms operating channel

## NSN 5996-01-026-1936

Radio Frequency Amplifier - Page 2 of 2



## **Maximum Continuous Operating Time In Hours:**

Not rated

**Connection Type And Location:** 

Receptacle, coaxial front and receptacle, coaxial rear and solder lug rear

**Connection Contact Type And Quantity:** 

2 receptacle, coaxial external and 4 solder lug external

**External Dc Operating Voltage In Volts:** 

25.0 single voltage

\_\_\_\_\_

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200