NSN 5996-01-032-5926

Overall Length: 1.609 inches

Overall Diameter:

Environmental Protection:

-54.0/+95.0 degrees celsius

Operating Tempurature Range:

1.067 inches

Explosion proof

Electronic Control Amplifier - Page 1 of 2



 $\label{thm:com/nsn/5996-01-032-5926} View \ Online \ at \ https://aerobasegroup.com/nsn/5996-01-032-5926$

Average Life Measurement:	
Not rated	
Basic Shape Style:	
Cylindrical	
Identification Designator:	
U-210914-8-10-1-2-a-82686	
Maximum Operating Altitude Rating:	
100000.0 feet	
Inclosure Type:	
Hermetically sealed	
Operating Control Method:	
Automatic	
Installation Design:	
Mechanical	
Control Type:	
Local	
Circuit Construction Type:	
Solid state	
Frequency Per Channel:	
400.0 hertz input channel	
Overall Gain:	
1.0 volts	
Impedance Rating Per Channel:	
220.000 kilohms input channel	
Signal Data Type Per Channel:	
Input channel servo	
Connection Type And Location:	
Err-060 glad hand quick disconnect	
Connection Contact Type And Quantity:	
6 tr int bs61 drain	
External Dc Operating Voltage In Volts:	
28.0 single voltage	
Features Provided:	
Zero shift capability	

NSN 5996-01-032-5926

Electronic Control Amplifier - Page 2 of 2



Special	Features:
----------------	-----------

Impedance rating per channel is for b input

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32200