

View Online at <https://aerobasegroup.com/nsn/5996-01-034-2142>

Overall Length:

6.000 inches

Overall Height:

5.000 inches

Overall Width:

1.620 inches

Environmental Protection:

Fungus proof and moisture proof

Vibration Resistance Range In Hertz:

+5.0/+15.0

Individual Section Quantity:

1

Vibration Resistance Amplitude:

0.15 inches total excursion

Shock Resistance Rating In Gravitational Units:

75.0

Operating Temperature Range:

+0.0/+71.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Identification Designator:

154097-1-24930

Phase Shift Angle In Deg:

10.0 input to output

Maximum Operating Altitude Rating:

10000.0 feet

Inclosure Type:

Encapsulated

Operating Control Method:

Automatic

Installation Design:

Panel

Control Type:

Remote

Circuit Construction Type:

Solid state

Switching Rate Per Second:

220

Frequency Per Channel:

3.12 gigahertz operating channel err-100

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

4.0 watts output

Signal Voltage Rating Per Channel:

Not rated

Overall Gain:

28.0 decibels

Impedance Rating Per Channel:

50.000 ohms input channel err-100

Maximum Continuous Operating Time In Hours:

50000.0

Shock Pulse Duration Time:

6.0 milliseconds

Connection Type And Location:

Receptacle, coaxial front and receptacle, coaxial front and receptacle, power right side

Connection Contact Type And Quantity:

1 receptacle, coaxial internal and 1 receptacle, coaxial internal and 6 receptacle, power external

External Dc Operating Voltage In Volts:

28.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200