

View Online at <https://aerobasegroup.com/nsn/5996-01-054-2820>

Overall Length:

1.756 inches

Overall Width:

1.600 inches

Environmental Protection:

Vibration and shock resistant

Vibration Resistance Range In Hertz:

+1.0/+2.5

Vibration Resistance Amplitude:

1.0 gravitational units

Shock Resistance Rating In Gravitational Units:

15.0

Operating Temperature Range:

-28.0/+65.0 degrees celsius

Average Life Measurement:

Indefinite

Basic Shape Style:

Rectangular or square

Inclosure Type:

Partially enclosed

Operating Control Method:

Automatic

Installation Design:

Rack

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

300.0 hertz operating channel and 100.0 hertz operating channel

Average Power Rating Per Channel:

100.0 milliwatts input

Signal Voltage Rating Per Channel:

13.500 volts output

Overall Gain:

40.0 decibels

Distortion Type And Percent:

0.4 amplitude

Indicator Device Type And Quantity:

1 meter

Maximum Continuous Operating Time In Hours:

40000.0

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Printed circuit bottom

External Dc Operating Voltage In Volts:

13.5 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200