## NSN 5996-01-073-6859

Radio Frequency Amplifier - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5996-01-073-6859



**Overall Length:** 2.380 inches **Overall Height:** 1.250 inches **Overall Width:** 1.880 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +5.0/+55.0 **Vibration Resistance Amplitude:** 2.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 20.0 **Operating Tempurature Range:** +0.0/+71.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** An/srd-19-02643 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Hermetically sealed Installation Design: Mechanical **Circuit Construction Type:** Solid state Frequency Per Channel: 30.0 megahertz operating channel err-100 **Variation Frequency Rating In Decibels:** 1.5 **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated Signal Voltage Rating Per Channel: 15.000 volts input **Overall Gain:** 13.0 decibels

## NSN 5996-01-073-6859

Radio Frequency Amplifier - Page 2 of 2



## Impedance Rating Per Channel:

50.000 ohms operating channel

**Maximum Continuous Operating Time In Hours:** 

Not rated

**Connection Type And Location:** 

Receptacle, coaxial left side and receptacle, coaxial right side

**Connection Contact Type And Quantity:** 

2 solder lug external

**External Dc Operating Voltage In Volts:** 

18.0 single voltage

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

Yes - demil/mli

Fiig:

A32200