NSN 5996-01-082-2927

Radio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-01-082-2927 **Overall Length:** 5.430 inches **Overall Height:** 2.250 inches **Overall Width:** 4.310 inches **Environmental Protection:** Fungus proof and moisture proof **Vibration Resistance Range In Hertz:** Not rated **Individual Section Quantity: Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -28.0/+65.0 degrees celsius **Average Life Measurement:** Hours **Average Life Rating In Hours:** 87600.0 **Basic Shape Style:** Rectangular or square **Identification Designator:** D270-00-580-3032 **Maximum Operating Altitude Rating:** 5000.0 feet **Inclosure Type:** Encased Installation Design: Mechanical **Circuit Construction Type:** Solid state Frequency Per Channel: 270.5 megahertz operating channel err-100 **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated Signal Voltage Rating Per Channel: 28.000 volts input

Overall Gain: 26.2 decibels

NSN 5996-01-082-2927

Radio Frequency Amplifier - Page 2 of 2



Impedance Rating Per Channel:

50.000 ohms input channel err-100

Maximum Continuous Operating Time In Hours:

Not rated

Connection Type And Location:

Receptacle, power front and receptacle, coaxial left side and receptacle, coaxial right side

Connection Contact Type And Quantity:

1 receptacle, power external and 1 receptacle, coaxial external and 1 receptacle, coaxial external

External Dc Operating Voltage In Volts:

28.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200