## NSN 5996-01-090-4682

Radio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-01-090-4682

Overall Length:
2.060 inches
Overall Height:
0.630 inches
Overall Width:
1.300 inches
Environmental Protection:
Moisture proof
Vibration Resistance Range In Hertz:
+5.0/+33.0
Vibration Resistance Amplitude:
0.15 gravitational units and 0.05 gravitational units
Shock Resistance Rating In Gravitational Units:
60.0
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
18-1242284-07397
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Mechanical
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
1.95 gigahertz operating channel and 4.05 gigahertz operating channel
Overall Gain:
16.5 decibels
Shock Pulse Duration Time:

Connection Type And Location:

Receptacle, coaxial left side and ground terminal right side and receptacle, coaxial right side and terminal stud right side

## NSN 5996-01-090-4682

Radio Frequency Amplifier - Page 2 of 2



## **Connection Contact Type And Quantity:**

1 ground terminal external and 2 receptacle, coaxial external and 1 terminal stud external

**External Dc Operating Voltage In Volts:** 

15.0 single voltage

**Criticality Code Justification:** 

Feat

**Special Features:** 

Used on electronic warfare equipment an/wlq-4 and an/wlr-8

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200