Radio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-01-090-4683

Overall Length:
2.130 inches
Overall Height:
0.840 inches
Overall Width:
1.500 inches
Environmental Protection:
Shock resistant and vibration
Vibration Resistance Range In Hertz:
+5.0/+33.0
Vibration Resistance Amplitude:
0.15 gravitational units
Shock Resistance Rating In Gravitational Units:
60.0
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Identification Designator:
Sd8-0926m-24539
Inclosure Type:
Hermetically sealed
Installation Design:
Mechanical
Circuit Construction Type:
Solid state
Frequency Per Channel:
530.0 megahertz operating channel err-100
Overall Gain:
16.0 decibels
Impedance Rating Per Channel:
Not rated
Maximum Continuous Operating Time In Hours:
Not rated
Shock Pulse Duration Time:
20.0 milliseconds
Connection Type And Location:
Receptacle, coaxial left side and receptacle, coaxial right side and receptacle, power left side and receptacle, power right side
Connection Contact Type And Quantity:

2 receptacle, coaxial external and 2 receptacle, power external

Radio Frequency Amplifier - Page 2 of 2



External Dc Operating Voltage In Volts:

15.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200