Radio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-01-122-5560

Over all Learning the
Overall Length:
4.000 inches
Overall Height:
0.850 inches
Overall Width:
0.850 inches
Environmental Protection:
Salt spray resistant and shock resistant and vibration
Vibration Resistance Range In Hertz:
+4.0/+33.0
Vibration Resistance Amplitude:
0.100 inches total excursion
Shock Resistance Rating In Gravitational Units:
50.0
Operating Tempurature Range:
-28.0/+85.0 degrees celsius
Average Life Measurement:
Hours
Basic Shape Style:
Rectangular or square
Identification Designator:
2622971-28527
Inclosure Type:
Encased
Installation Design:
Mechanical
Circuit Construction Type:
Solid state
Impedance Rating Per Channel:
50.000 ohms operating channel
Maximum Continuous Operating Time In Hours:
10000.0
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Single panel jack left side and single panel jack right side and solder lug left side
Connection Contact Type And Quantity:
2 solder lug external
External Dc Operating Voltage In Volts:
20.0 single voltage
Shelf Life:
N/a

NSN 5996-01-122-5560

Radio Frequency Amplifier - Page 2 of 2



Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200