NSN 5996-01-144-3483

Radio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-01-144-3483 **Overall Length:** 3.060 inches **Overall Height:** 0.610 inches **Overall Width:** 1.300 inches **Environmental Protection:** Shock resistant and vibration **Vibration Resistance Range In Hertz:** +30.0/+33.0 **Shock Resistance Rating In Gravitational Units:** 60.0 **Operating Tempurature Range:** -0.0/+70.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Operating Control Method:** Automatic **Installation Design:** Rack **Circuit Construction Type:** Solid state Frequency Per Channel: 1.976 gigahertz operating channel and 4.022 gigahertz operating channel **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated **Signal Voltage Rating Per Channel:**

Not rated **Overall Gain:** 23.0 decibels **Impedance Rating Per Channel:** 50.000 ohms operating channel **Maximum Continuous Operating Time In Hours:** Not rated

NSN 5996-01-144-3483

Radio Frequency Amplifier - Page 2 of 2



Shock Pulse Duration Time:

20.0 milliseconds

Connection Type And Location:

Connector, plug left side and connector, plug right side

Connection Contact Type And Quantity:

1 connector, plug external and 1 connector, plug external

External Dc Operating Voltage In Volts:

15.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200