

View Online at <https://aerobasegroup.com/nsn/5996-01-166-7386>

Overall Length:

Between 2.100 inches and 2.140 inches

Overall Height:

Between 0.820 inches and 0.860 inches

Overall Width:

Between 1.480 inches and 1.520 inches

Environmental Protection:

Moisture proof and salt spray resistant and shock resistant and vibration

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Individual Section Quantity:

1

Vibration Resistance Amplitude:

15.0 gravitational units

Shock Resistance Rating In Gravitational Units:

30.0

Operating Temperature Range:

-54.0/+71.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Identification Designator:

292403p1-94117

Maximum Operating Altitude Rating:

Not rated

Inclosure Type:

Encased

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

10.0 megahertz operating channel and 500.0 megahertz operating channel

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

158.0 milliwatts output

Signal Voltage Rating Per Channel:

Not rated

Overall Gain:

2.0 decibels

Maximum Continuous Operating Time In Hours:

Not rated

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Receptacle, coaxial front and receptacle, power front and terminal stud front and receptacle, coaxial rear

Connection Contact Type And Quantity:

2 receptacle, coaxial external and 1 receptacle, power external and 1 terminal stud external

External Dc Operating Voltage In Volts:

15.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200