

View Online at <https://aerobasegroup.com/nsn/5996-01-182-8294>

Inclosure Material:

Steel

Overall Length:

6.300 inches

Overall Height:

0.750 inches

Overall Width:

Between 1.950 inches and 2.090 inches

Environmental Protection:

Fungus proof and moisture proof and salt spray resistant and shock resistant and vibration

Vibration Resistance Range In Hertz:

+5.0/+200.0

Vibration Resistance Amplitude:

10.0 gravitational units

Shock Resistance Rating In Gravitational Units:

40.0

Operating Temperature Range:

-25.0/+150.0 degrees fahrenheit

Average Life Measurement:

Hours

Average Life Rating In Hours:

100000.0

Basic Shape Style:

Rectangular or square

Phase Shift Angle In Deg:

1.0 input to output

Maximum Operating Altitude Rating:

10000.0 feet

Inclosure Type:

Encased

Operating Control Method:

Automatic

Installation Design:

Mechanical

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

700.0 megahertz 2nd output channel err-100

Signal Voltage Rating Per Channel:

15.000 volts input

Overall Gain:

47.0 decibels

Impedance Rating Per Channel:

50.000 ohms input channel err-100

Shock Pulse Duration Time:

6.0 milliseconds

Connection Type And Location:

Receptacle, coaxial front and receptacle, coaxial left side and receptacle, coaxial right side and solder stud right side

Connection Contact Type And Quantity:

3 receptacle, coaxial external and 2 solder stud external

External Dc Operating Voltage In Volts:

15.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200