## NSN 5996-01-340-6010

Radio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-01-340-6010
Overall Length:
Between 0.345 inches and 0.365 inches
Overall Diameter:
Between 0.335 inches and 0.370 inches
Environmental Protection:
Moisture proof and explosion proof and shock resistant and vibration
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
Storage Tempurature Range:
-65.0/+125.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Cylindrical
Identification Designator:
1423-00-000-1454
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
50.0 megahertz operating channel and 150.0 megahertz operating channel
Overall Gain:
25.0 decibels
Impedance Rating Per Channel:
50.000 ohms input channel err-10050.000 ohms output channel err-100
Connection Type And Location:
Pin bottom
Connection Contact Type And Quantity:
4 pin external
External Dc Operating Voltage In Volts:
12.0 single voltage
Criticality Code Justification:
Feat

reat

Special Features:

Nuclear hardness critical item

## NSN 5996-01-340-6010

Radio Frequency Amplifier - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200