NSN 5996-01-361-4430

Radio Frequency Amplifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5996-01-361-4430 **Overall Length:** 1.961 inches **Overall Height:** 1.000 inches **Overall Width:** 1.600 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 **Vibration Resistance Amplitude:** 15.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 100.0 **Operating Tempurature Range:** -35.0/+85.0 degrees celsius **Storage Tempurature Range:** -55.0/+100.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** 5895-01-180-1415 control computer **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 10000.0 feet **Inclosure Type:** Encased **Operating Control Method:** Automatic Installation Design: Mechanical **Control Type:** Remote **Circuit Construction Type:**

Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
40.0 megahertz operating channel and 100.0 megahertz operating channel
Overall Gain:
26.0 decibels
Shock Pulse Duration Time:
6.0 milliseconds
Connection Type And Location:
Receptacle, coaxial front and receptacle, coaxial right side and solder lug right side

NSN 5996-01-361-4430

Radio Frequency Amplifier - Page 2 of 2



Connection Contact Type And Quantity:

2 receptacle, coaxial external and 2 solder lug external

External Dc Operating Voltage In Volts:

15.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200